

## Technical Specifications

### Mechanical

<b>Dimensions</b>	202.9 x 76 x 33 mm (8 x 3 x 1.3")
<b>Weight</b>	Device: 320 g (11.3 oz) Wall mount: 45 g (1.6 oz)
<b>Enclosure material</b>	Polycarbonate

### Hardware

<b>Management interface</b>	Ethernet In-Band
<b>Networking interface</b>	(8) GbE RJ45 ports
<b>PoE interface</b>	(7) PoE/PoE+ (Pins 1, 2+; 3, 6-)
<b>Total non-blocking throughput</b>	8 Gbps
<b>Power method</b>	54V, 3.9A power adapter (Not included) PoE++ (Pins 4, 5+; 7, 8-)
<b>Power supply</b>	54V, external, 1.1A/60W
<b>Supported voltage range</b>	44—57V DC
<b>Total available PoE</b>	60W PoE++ input: 45W DC adapter input: 52W Passive PoE adapter input: 45W
<b>Max. PoE+ wattage per port by PSE</b>	30W
<b>Button</b>	Factory reset
<b>Operating temperature</b>	-15 to 45° C (5 to 113° F)
<b>Operating humidity</b>	10 to 90% noncondensing
<b>Certifications</b>	CE, FCC, IC

### LEDs

<b>System</b>	Status
<b>Ethernet</b>	PoE Link/activity