

Display

Brightness (ANSI lumens)	4000
Resolution	SVGA (800x600)
Native Aspect Ratio	4:3
Contrast Ratio (FOFO)	20,000:1
Display Color	30-bit (1.07 billion colors)
Light Source	Lamp
Light Source Life	a. Normal 6000 hrs, c. SmartEco 10000 hrs, d. LampSave 15000 hrs, b. ECO 10000 hrs

Optical

Throw Ratio	1.96~2.15
Zoom Ratio	1.1x
Lens	F/# = 2.56 ~ 2.68, f=22~24.1mm
Projection Offset (Full-Height)	110%
Keystone Adjustment	1D, (Auto) Vertical \pm 40 degrees

Picture

Picture Modes	3D, Bright, Infographic, Presentation, Spreadsheet, sRGB, User 1, User 2
---------------	---

Compatibility

Resolution Support	VGA(640 x 480) to WUXGA_RB(1920 x 1200) *RB=Reduced blanking
Horizontal Frequency	15K~102KHz

I/O Interface

PC in (D-sub 15pin)	(x1)
Monitor out (D-sub 15pin)	(x1)

Composite Video in (RCA)	(x1)
S-Video in (Mini DIN 4pin)	(x1)
HDMI in	(x2), HDMI-1 (1.4a/HDCP1.4), HDMI-2 (1.4a/HDCP1.4)
USB Type A	(x1)
USB Type Mini B	(x1)
RS232 in (DB-9pin)	(x1)

Audio

Speaker	(x1), 10W
Audio in (3.5mm Mini Jack)	(x1)
Audio out (3.5mm Mini Jack)	(x1)

Environment

Operating Temperature	0~40°C
Power Supply	AC 100 to 240 V, 50/60 Hz
Typical Power Consumption (110V)	260W/110V
Acoustic Noise (Typ./Eco.)(dB)	34/29

Accessories

Remote Control w/ Battery	RCX016
Power Cord (by region)	x1 (1.8M)
VGA(D-sub 15pin) Cable	1 (1.5m)
3D Glasses	(Optional), DGD5
Quick Start Guide	(x1) 21L
Warranty Card (by region)	Yes
Universal Ceiling Mount	(Optional), CM00G3

Dimension & Weight

Dimensions (WxHxD) (mm) 296 x120 x221

Net Weight (kg) 2.3

Projection System

Projection System DLP